



UNICABLE, INC
"POWERING THE WORLD"



Stock & Custom Catalog



UNICABLE, Inc.

About Our Company

Since 1984, UNICABLE has been a quality supplier of power supply cords, cordsets, wiring harnesses and cable assemblies to companies in the electronics and appliance industries of the U.S. and around the world. Our success and growth reflects our high level of commitment to our customers to provide quality parts with responsive customer service. Engineering, Production and Customer Service work closely together with our suppliers, approval agencies and customers to make the most reliable product as efficiently as possible. We have developed strict Q/C policies to ensure production parts will meet or exceed our customers' requirements and agency standards. In addition to our standard parts, we offer custom tools for plugs, connectors, and strain reliefs made to your specifications with one of the lowest cost and quick turnaround times in the industry. Our multiple FOB points and warehouses enable us to offer our customers a delivery program that best suits their needs, whether they are in the U.S. or abroad. Our sales staff is eager to find how we can best serve you.



Bowling Green , Kentucky



Cypress, California



Unicom Limited

Highlights

• RELIABILITY

We understand the importance of having a supplier you can count on to deliver quality parts on time. UNICABLE has been providing cordsets and cable assemblies to many top manufacturers in the computer, electronics, appliance, medical and industrial product industries. When demands arise, we take action to meet the needs of our customers.

• QUALITY

You can rest assured with our excellent quality record and ISO 9001:2000 certification at the manufacturing facility in Dong Guan, China. UNICABLE goes the extra mile in quality engineering. We use top quality construction and materials for maximum safety and performance to exceed approval agency requirements. Stringent IQC, IPQC, & FQC standards ensure excellent product. With 100% inspection and testing, our record speaks for itself.

• VALUE

ALL UNICABLE products come to you with the highest quality at the most reasonable price. Without sacrificing quality, we minimize our costs to quote competitively. For the perfect blend of offshore manufacturing and US service, contact UNICABLE.

• EXPERIENCE

We have learned much in this changing market over the past two decades. With major shifts in manufacturing and varying demands, we remain stronger than ever. The manufacturing facility in China produces exclusively for Unicable, giving us a major advantage over our competitors. Put our 20 years of experience in the cordset industry to work for you.

• BROAD PRODUCT LINE

Our wide selection of North American plugs and connectors give you various styles to choose from. We offer hospital grade, GFCI, shrouded and piggyback plugs on both PVC and rubber cordage. A number of different IEC plugs and connectors in various styles are also available. Exporting your product? UNICABLE's International plugs in a variety of country configurations are available both from stock and as custom.

• DELIVERY PROGRAMS

UNICABLE offers JIT, Kan-Ban, and stocking programs to meet your needs. For your global locations, we can ship directly from Hong Kong. With warehouse locations in Kentucky and California, we are ready to serve you. Put our experience in custom delivery programs to work, and call our sales team today.

• CUSTOM TOOLING

High Quality, quick-turn around tooling is available at low cost on strain reliefs, plugs, connectors and accessories to meet your custom requirements.

• CUSTOM SERVICES

Whether it's bar code, warning or other custom labeling, special packaging, special accessories or hardware you need, UNICABLE can work with you on your individual requirements. For new product design or current product improvement troubleshooting, our engineering and sales departments can work with you to develop solutions.

Table of Contents

1. Stock Power Supply Cords

A. Index.....	4
B. 3 Conductor OEM Power Supply Cords	
North American Color Code.....	6
North American Outdoor Use.....	7
North American Rubber.....	8
CEE Color Code.....	9
Parallel Conductors, Non-Jacketed/Single Insulation.....	10
2 Conductor Power Supply Cords	
North American Color Code.....	10
Parallel Conductors, Non-Jacketed/Single Insulation.....	11
3 Conductor Electronic Power Supply Cords.....	12-13
3 Conductor Detachable Power Supply Cords.....	14-15
2 Conductor Detachable Power Supply Cords.....	15
3 Conductor Electronic Jumper Cords	
North American.....	17
International.....	18
3 Conductor Hospital Grade Power Supply Cords.....	19-20
C. International Power Supply Cords	
Continental Europe.....	21-22
Switzerland.....	23
UK (Great Britain).....	23
Denmark.....	24
Italy.....	24
Australia/New Zealand.....	25
Japan.....	26
China.....	27
Israel.....	27
Argentina.....	28
South Africa/India.....	28

2. Custom Power Supply Cords

A. How To Design a Power Cord/Harness.....	29
B. Plugs/Connectors.....	31-64
C. Wire Types.....	65-73
D. Molded Strain Reliefs.....	74-78
E. How to Specify Power Supply Cords.....	79-80

3. Molded Cable Assemblies

A. Molded Cable Assemblies.....	81
---------------------------------	----

4. Technical Information

A. International Approval and Standard Agencies.....	82
B. International Wire Coding Systems.....	83
C. UL Cord Type Designations.....	84
D. Construction and Ratings of UL Cord Types.....	84-85
E. Construction and Ratings of CEE and METI Cord Types.....	86-88
F. IEC 60320 Configurations.....	89
G. Wire & Cable Terminology & Abbreviations.....	90-91
H. NEMA Configurations.....	92

Plug & Connector Index

Plug No.	Page No.	Plug No.	Page No.
UC-001, UC-01A, UC-01B, UC-002	31	UC-09I, UC-09A, UC-09AI, UC-9BI	48
UC-02A, UC-02B, UC-02C, UC-02D	32	UC-09CI, UC-010, UC-011, UC-014	49
UC-003, UC-03A, UC-03C, UC-03C/H	33	UC-018, UC-018A, UC-018AL	50
UC-03C/U, UC-03D, UC-03E, UC-03F	34	UC-018G, UC-018L, UC-020	51
UC-03H, UC-004, UC-04A	35	UC-021, UC-022, UC-026, UC-028	52
UC-04B, UC-04C, UC-04D	36	UC-032, UC-032I, UC-032R, UC-032RI, UC-033	53
UC-04E, UC-04M	37	UC-033I, UC-033R, UC-033RI, UC-034, UC-035	54
UC-005, UC-05I, UC-05A	38	UC-040, UC-041, UC-051, UC-052, UC-053	55
UC-05AI, UC-05C, UC-05CI, UC-05E	39	UC-054, UC-055, UC-056, UC-071	56
UC-05P, UC-006, UC-06I, UC-06A	40	UC-071N, UC-071S, UC-071X, UC-071XA	57
UC-06AI, UC-06C, UC-06CI, UC-06L	41	UC-071Y, UC-071YA, UC-072, UC-073	58
UC-06LI, UC-06M, UC-06MI, UC-06ML	42	UC-074, UC-077, UC-701, UC-811	59
UC-06MLI, UC-07A, UC-07B, UC-07C	43	UC-812, UC-813, UC-814, UC-821	60
UC-07D, UC-07F, UC-07G	44	UC-822, UC-823, UC-824, UC-830	61
UC-07H, UC-008, UC-08B	45	UC-831, UC-832, UC-834, UC-837	62
UC-08C, UC-08CS	46	UC-838, UC-840, UC-841, UC-861	63
UC-08D, UC-08F, UC-08BT, UC-009	47	UC-871, UC-872, UC-881, UC-882, UC-892	64

Stock Power Supply Cord Index

Part No.	Page No.	Part No.	Page No.	Part No.	Page No.	Part No.	Page No.
1218-06F-BB	11	4635-02M-BB	18	6650-02M-BB	14	8220-25M-BB	25
1218-06F-WH	11	4650-76I-BB	14	6650-03M-BB	14	8225-25M-BB	25
1218-08F-BB	11	4680-04M-BB	19	6690-02M-BB	13	8250-25M-BB	25
1236-67I-BB	10	4680-04M-GG	19	6692-02M-BB	15	8250-25M-GG	25
1238-67I-BB	10	4692-02M-BB	16	6800-02M-BB	9	8300-25M-BB	26
1840-25M-BB	16	4800-06F-BB	5	6800-03M-BB	9	8301-25M-BB	26
3800-06F-BB	5	4800-08F-BB	5	6830-02M-BB	12	8320-25M-BB	26
3800-06F-GG	5	4800-08F-GG	5	6835-01M-BB	17	8325-25M-BB	26
3800-08F-BB	5	4800-10F-BB	5	6850-02M-BB	14	8350-25M-BB	26
3800-08F-GG	5	4810-03M-BB	20	6850-03M-BB	14	8351-25M-BB	26
3810-64I-BB	9	4810-03M-GG	20	6890-02M-BB	13	8400-25M-BB	23
3810-64I-GG	9	4811-03M-GG	20	6892-02M-BB	15	8450-25M-BB	23
3812-08F-BB	9	4815-02M-BB	9	7200-15F-BB	6	8500-25M-BB	23
3822-63I-BB	10	4815-03M-BB	9	7209-08F-BB	6	8501-25M-BB	23
3830-08F-BB	12	4820-03M-GG	20	7404-10F-BB	7	8530-25M-BB	27
3835-01M-BB	17	4822-63I-BB	10	7601-64I-BB	7	8535-25M-BB	27
3835-02M-BB	17	4830-02M-BB	12	7601-10F-BB	7	8550-25M-BB	23
3850-76I-BB	14	4835-01M-BB	18	7604-10F-BB	7	8600-25M-BB	24
3850-76I-BB/NA	14	4835-02M-BB	18	7608-08F-BB	6	8650-25M-BB	24
3890-08F-BB	13	4850-25M-BB	14	7801-64I-BB	7	8700-25M-BB	28
3892-02M-BB	15	4870-03M-GG	19	7801-10F-BB	7	8750-25M-BB	28
4260-76I-BB	15	4880-03M-BB	19	7804-64I-BB	7	8800-25M-BB	24
4400-06F-BB	5	4880-03M-GG	19	7804-10F-BB	7	8801-25M-BB	24
4400-08F-BB	5	4881-03M-GG	19	8100-25M-BB	21	8850-25M-BB	24
4450-02M-BB	14	4892-02M-BB	16	8100-25M-GG	21	8900-25M-BB	27
4480-04M-GG	19	5835-01M-BB	17	8110-25M-BB	21	8950-25M-BB	27
4600-06F-BB	5	5850-02M-BB	14	8120-25M-BB	22	8960-25M-BB	28
4600-08F-BB	5	5890-08F-BB	13	8125-25M-BB	22	8965-25M-BB	28
4600-10F-BB	5	5892-02M-BB	15	8145-02M-BB	18	9400-08F-BB	8
4615-02M-BB	9	6450-02M-BB	14	8150-25M-BB	21	9400-10F-BB	8
4615-03M-BB	9	6450-03M-BB	14	8150-25M-GG	21	9600-08F-BB	8
4622-04M-BB	20	6600-03M-BB	9	8192-25M-BB	22	9600-10F-BB	8
4262-76I-BB	16	6630-02M-BB	12	8192-25M-GG	22	9800-08F-BB	8
4630-02M-BB	12	6635-01M-BB	17	8200-25M-BB	25	9800-10F-BB	8
						9804-08F-BB	8

3 Conductor Power Supply Cords

North American Color Code



TYPE SVT

PVC Jacket,
60°C/105°C



End One: UC-004 (NEMA5-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
3800-06F-BB	10A/125V	18/3 (41x34)	NA	6'/1.8	0.255	150	44
3800-06F-GG	10A/125V	18/3 (41x34)	NA	6'/1.8	0.255	150	44
3800-08F-BB	10A/125V	18/3 (41x34)	NA	8'/2.4	0.255	100	42
3800-08F-GG	10A/125V	18/3 (41x34)	NA	8'/2.4	0.255	100	42

Standard Bulk Packaged

TYPE SJT

PVC Jacket,
60°C/105°C



End One: UC-004 (NEMA 5-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4800-06F-BB	10A/125V	18/3 (41x34)	NA	6'/1.8	0.307	100	38
4800-06F-GG	10A/125V	18/3 (41x34)	NA	6'/1.8	0.307	100	38
4800-08F-BB	10A/125V	18/3 (41x34)	NA	8'/2.4	0.307	100	49
4800-08F-GG	10A/125V	18/3 (41x34)	NA	8'/2.4	0.307	100	49
4800-10F-BB	10A/125V	18/3 (41x34)	NA	10'/3.0	0.307	75	45
4600-06F-BB	13A/125V	16/3 (26x30)*	NA	6'/1.8	0.334	100	46
4600-08F-BB	13A/125V	16/3 (26x30)*	NA	8'/2.4	0.334	50	31
4600-10F-BB	13A/125V	16/3 (26x30)*	NA	10'/3.0	0.334	50	39
4400-06F-BB	15A/125V	14/3 (41x30)	NA	6'/1.8	0.375	75	50
4400-08F-BB	15A/125V	14/3 (41x30)	NA	8'/2.4	0.375	50	41

Standard Bulk Packaged

*Stock also produced with Alternate Stranding of 65x34

NOTE: BB = Black, GG = Gray

3 Conductor Power Supply Cords

North American Color Code--Outdoor Use



TYPE STW

Outdoor Use,
Water Resistant,
PVC Jacket, 60°C/105°C



End One: UC-07F (NEMA 5-20P)
End Two: Remove Outer Jacket 6", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
7200-15F-BB <i>Coil & Tie Packaged</i>	20A/125V	12/3 (65x30)	NA	15/4.6	0.622	10	37

TYPE SJTOW

Outdoor Use,
Oil & Water Resistant,
PVC Jacket, 60°C/105°C



End One: UC-07H (NEMA 6-20P)
End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
7209-08F-BB <i>Standard Bulk Packaged</i>	20A/250V	12/3 (65x30)	NA	8/2.4	0.429	25	34

TYPE SJTOW

Outdoor Use,
Oil & Water Resistant,
PVC Jacket, 60°C/105°C



End One: UC-07G (NEMA 6-15P)
End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
7608-08F-BB <i>Standard Bulk Packaged</i> <i>*Stock also produced with Alternate Stranding of 65x34</i>	13A/250V	16/3 (26x30)*	NA	8/2.4	0.334	50	34

NOTE: BB = Black, GG = Gray

3 Conductor Power Supply Cords

North American Color Code--Outdoor Use



TYPE SJTW

Outdoor Use,
Water Resistant,
PVC Jacket, 60°C/105°C



End One: UC-004 (NEMA 5-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
7801-64I-BB	10A/125V	18/3 (41x34)	NA	6'4"/1.9	0.307	100	40
7801-10F-BB	10A/125V	18/3 (41x34)	NA	10'/3.0	0.307	75	46
7601-64I-BB	13A/125V	16/3 (26x30)*	NA	6'4"/1.9	0.334	100	49
7601-10F-BB	13A/125V	16/3 (26x30)*	NA	10'/3.0	0.334	50	40

Standard Bulk Packaged

*Stock also produced with Alternate Stranding of 65x34

TYPE SJTOW

Outdoor Use,
Oil & Water Resistant,
PVC Jacket, 60°C/105°C



End One: UC-004 (NEMA 5-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
7804-64I-BB	10A/125V	18/3 (41x34)	NA	6'4"/1.9	0.307	100	40
7804-10F-BB	10A/125V	18/3 (41x34)	NA	10'/3.0	0.307	75	46
7604-10F-BB	13A/125V	16/3 (26x30)*	NA	10'/3.0	0.334	50	38
7404-10F-BB	15A/125V	14/3 (41x30)	NA	10'/3.0	0.375	50	52

Standard Bulk Packaged

*Stock also produced with Alternate Stranding of 65x34

NOTE: BB = Black, GG = Gray



UNICABLE
www.unicable.com

California: (800) GET-CORD
Kentucky: (800) FOR-CORD

FAX: (714) 761-0569
FAX: (270) 843-8888

3 Conductor Power Supply Cords

North American Color Code--Rubber



TYPE SJ

Rubber Jacket, 90°C



End One: UC-04D (NEMA 5-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
9800-08F-BB	10A/125V	18/3 (41x34)	NA	8'2.4	0.307	75	43
9800-10F-BB	10A/125V	18/3 (41x34)	NA	10'3.0	0.307	50	35
9600-08F-BB	13A/125V	16/3 (65x34)	NA	8'2.4	0.334	50	35
9600-10F-BB	13A/125V	16/3 (65x34)	NA	10'3.0	0.334	50	43
9400-08F-BB	15A/125V	14/3 (41x30)	NA	8'2.4	0.375	50	45
9400-10F-BB	15A/125V	14/3 (41x30)	NA	10'3.0	0.375	40	44

Standard Bulk Packaged

TYPE SJO

Oil Resistant

Rubber/CPE Jacket, 90°C



End One: UC-04D (NEMA 5-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
9804-08F-BB	10A/125V	18/3 (41x34)	NA	8'2.4	0.307	75	44

Standard Bulk Packaged

NOTE: BB = Black, GG = Gray



3 Conductor Power Supply Cords

CEE Color Code



TYPE SJT

Foil Shielded,
PVC Jacket, 60°C/105°C



End One: UC-004 (NEMA 5-15P)
End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
6800-02M-BB	10A/125V	18/3 (41x34)	CEE	6'7"/2.0	0.343	100	48
6800-03M-BB	10A/125V	18/3 (41x34)	CEE	9'10"/3.0	0.343	75	53
6600-03M-BB	13A/125V	16/3 (65x34)	CEE	9'10"/3.0	0.360	50	43

Braided Shield is available upon request as a custom item.
Standard Bulk Packaged

TYPE SVT

Unshielded,
PVC Jacket, 60°C/105°C



End One: UC-004 (NEMA 5-15P)
End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
3810-64I-BB	10A/125V	18/3 (41x34)	CEE	6'4"/1.9	0.255	100	32
3810-64I-GG	10A/125V	18/3 (41x34)	CEE	6'4"/1.9	0.255	100	32
3812-08F-BB	10A/125V	18/3 (41x34)	CEE	8'2"/2.4	0.255	100	41

Standard Bulk Packaged

TYPE SJT

Unshielded,
PVC Jacket, 60°C/105°C



End One: UC-004 (NEMA 5-15P)
End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4815-02M-BB	10A/125V	18/3 (41x34)	CEE	6'7"/2.0	0.307	100	41
4815-03M-BB	10A/125V	18/3 (41x34)	CEE	9'10"/3.0	0.307	75	45
4615-02M-BB	13A/125V	16/3 (26x30)*	CEE	6'7"/2.0	0.334	100	51
4615-03M-BB	13A/125V	16/3 (26x30)*	CEE	9'10"/3.0	0.334	50	37

Standard Bulk Packaged

*Stock also produced with Alternate Stranding of 65x34

NOTE: BB = Black, GG = Gray



UNICABLE
www.unicable.com

California: (800) GET-CORD
Kentucky: (800) FOR-CORD

FAX: (714) 761-0569
FAX: (270) 843-8888

3 Conductor Power Supply Cords

Parallel Conductors, Non-Jacketed/Single Insulation



TYPE SPT-2

PVC Insulated, 60°C/105°C



End One: UC-004 (NEMA 5-15P)

End Two: Split Leads 1 1/4", Strip & Twist 2/5"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
1238-67I-BB	10A/125V	18/3 (41x34)	Black	6'7"/2.0	0.142/0.339	100	33
1236-67I-BB	13A/125V	16/3 (65x34)	Black	6'7"/2.0	0.154/0.382	100	38

Standard Bulk Packaged

2 Conductor Power Supply Cords

North American Color Code



TYPE SVT

PVC Jacket, 60°C/105°C



End One: UC-008 (NEMA 1-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
3822-63I-BB	10A/125V	18/2 (41x34)	NA	6'3"/1.9	0.248	100	24

Standard Bulk Packaged

TYPE SJT

PVC Jacket, 60°C/105°C



End One: UC-008 (NEMA 1-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4822-63I-BB	10A/125V	18/2 (41x34)	NA	6'3"/1.9	0.280	100	32

Standard Bulk Packaged

NOTE: BB = Black, GG = Gray
Ground Wire is Green



2 Conductor Power Supply Cords

Parallel Conductors, Non-Jacketed/Single Insulation



TYPE SPT-2

PVC Insulated, 60°C/105°C



End One: UC-001 (NEMA 1-15P)

End Two: Split Leads 1 1/4", Strip & Twist 2/5"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
1218-06F-BB	10A/125V	18/2 (41x34)	Black	6'1.8	0.139/0.271	250	48
1218-06F-WH	10A/125V	18/2 (41x34)	White	6'1.8	0.139/0.271	250	48
1218-08F-BB	10A/125V	18/2 (41x34)	Black	8'2.4	0.139/0.271	200	53

Standard Bulk Packaged

NOTE: BB = Black, GG = Gray, BR = Brown



UNICABLE
www.unicable.com

California: (800) GET-CORD
Kentucky: (800) FOR-CORD

FAX: (714) 761-0569
FAX: (270) 843-8888

3 Conductor Electronic Power Supply Cords



TYPE SJT

Foil Shielded, PVC Jacket, 60°C



End One: UC-005 (IEC 60320/C13)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
6830-02M-BB	10A-125V/250V	18/3 (41x34)	CEE	6'7"/2.0	0.343	100	47
6630-02M-BB	13A-125V/250V	16/3 (65x34)	CEE	6'7"/2.0	0.360	100	57

Braided Shield is available upon request as a custom item.
Standard Bulk Packaged

TYPE SVT

Unshielded, PVC Jacket, 60°C



End One: UC-005 (IEC 60320/C13)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
3830-08F-BB	10A-125V/250V	18/3 (41x34)	CEE	8'/2.4	0.255	100	39

Standard Bulk Packaged

TYPE SJT

Unshielded, PVC Jacket, 60°C



End One: UC-005 (IEC 60320/C13)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4830-02M-BB	10A-125V/250V	18/3 (41x34)	CEE	6'7"/2.0	0.307	100	42
4630-02M-BB	13A-125V/250V	16/3 (26x30)*	CEE	6'7"/2.0	0.334	100	50

Standard Bulk Packaged

*Stock also produced with Alternate Stranding of 65x34

NOTE: BB = Black, GG = Gray
*Carries both 125V & 250V Rating



3 Conductor Electronic Power Supply Cords



TYPE SVT

Foil Shielded, PVC Jacket, 60°C



End One: UC-006 (IEC 60320/C13)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
5890-08F-BB	10A-125V/250V	18/3 (41x34)	CEE	8'2.4	0.263	100	44

Braided Shield is available upon request as a custom item.
Standard Bulk Packaged

TYPE SJT

Foil Shielded, PVC Jacket, 60°C



End One: UC-006 (IEC 60320/C13)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
6890-02M-BB	10A-125V/250V	18/3 (41x34)	CEE	6'7"/2.0	0.343	100	51
6690-02M-BB	13A-125V/250V	16/3 (65x34)	CEE	6'7"/2.0	0.360	100	60

Braided Shield is available upon request as a custom item.
Standard Bulk Packaged

TYPE SVT

Unshielded, PVC Jacket, 60°C



End One: UC-006 (IEC 60320/C13)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
3890-08F-BB	10A-125V/250V	18/3 (41x34)	CEE	8'2.4	0.255	100	39

Standard Bulk Packaged

NOTE: BB = Black, GG = Gray
*Carries both 125V & 250V Rating



UNICABLE
www.unicable.com

California: (800) GET-CORD
Kentucky: (800) FOR-CORD

FAX: (714) 761-0569
FAX: (270) 843-8888

3 Conductor Detachable Power Supply Cords



TYPE SVT

Foil Shielded, PVC Jacket, 60°C



End One: UC-004 (NEMA 5-15P)

End Two: UC-005 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
5850-02M-BB	10A/125V	18/3 (41x34)	CEE	6'7"/2.0	0.263	100	40

Braided Shield is available upon request as a custom item.
Standard Hank Packaged

TYPE SJT

Foil Shielded, PVC Jacket, 60°C



End One: UC-004 (NEMA 5-15P)

End Two: UC-005 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
6850-02M-BB	10A/125V	18/3 (41x34)	CEE	6'7"/2.0	0.343	100	53
6850-03M-BB	10A/125V	18/3 (41x34)	CEE	9'10"/3.0	0.343	50	39
6650-02M-BB	13A/125V	16/3 (65x34)	CEE	6'7"/2.0	0.360	100	63
6650-03M-BB	13A/125V	16/3 (65x34)	CEE	9'10"/3.0	0.360	50	44
6450-02M-BB	15A/125V	14/3 (41x30)	CEE	6'7"/2.0	0.390	50	38
6450-03M-BB	15A/125V	14/3 (41x30)	CEE	9'10"/3.0	0.390	50	54

Braided Shield is available upon request as a custom item.
Standard Hank Packaged

TYPE SVT

Unshielded, PVC Jacket, 60°C



End One: UC-004 (NEMA 5-15P)

End Two: UC-005 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
3850-76I-BB	10A/125V	18/3 (41x34)	CEE	7'6"/2.3	0.255	100	43
3850-76I-BB/NA	10A/125V	18/3 (41x34)	NA	7'6"/2.3	0.255	100	43

Standard Hank Packaged

TYPE SJT

Unshielded, PVC Jacket, 60°C



End One: UC-004 (NEMA 5-15P)

End Two: UC-005 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4850-25M-BB	10A/125V	18/3 (41x34)	CEE	8'2"/2.5	0.307	75	43
4650-76I-BB	13A/125V	16/3 (26x30)*	CEE	7'6"/2.3	0.334	50	33
4450-02M-BB	15A/125V	14/3 (41x30)	CEE	6'7"/2.0	0.375	50	37

Standard Hank Packaged

*Stock also produced with Alternate Stranding of 65x34

NOTE: BB = Black, GG = Gray



3 Conductor Detachable Power Supply Cords



TYPE SJT

Unshielded, PVC Jacket, 60°C



End One: UC-07H (NEMA 6-20P)
End Two: UC-033 (IEC 60320/C19)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4260-76I-BB	20A/250V	12/3 (65x30)	CEE	7'6"/>2.3	0.429	25	33
Standard Hank Packaged							

TYPE SVT

Foil Shielded, PVC Jacket, 60°C



End One: UC-004 (NEMA 5-15P)
End Two: UC-006 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
5892-02M-BB	10A/125V	18/3 (41x34)	CEE	6'7"/>2.0	0.263	100	43
Braided Shield available upon request as a custom item. Standard Hank Packaged							

TYPE SJT

Foil Shielded, PVC Jacket, 60°C



End One: UC-004 (NEMA 5-15P)
End Two: UC-006 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
6892-02M-BB	10A/125V	18/3 (41x34)	CEE	6'7"/>2.0	0.343	100	54
6692-02M-BB	13A/125V	16/3 (65x34)	CEE	6'7"/>2.0	0.360	100	57
Braided Shield available upon request as a custom item. Standard Hank Packaged							

TYPE SVT

Unshielded, PVC Jacket, 60°C



End One: UC-004 (NEMA 5-15P)
End Two: UC-006 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
3892-02M-BB	10A/125V	18/3 (41x34)	CEE	6'7"/>2.0	0.255	100	38
Standard Hank Packaged							

NOTE: BB = Black, GG = Gray



UNICABLE
www.unicable.com

California: (800) GET-CORD
Kentucky: (800) FOR-CORD

FAX: (714) 761-0569
FAX: (270) 843-8888

3 & 2 Conductor Detachable Power Supply Cords



TYPE SJT

Unshielded, PVC Jacket, 60°C



End One: UC-004 (NEMA 5-15P)

End Two: UC-006 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4892-02M-BB	10A/125V	18/3 (41x34)	CEE	6'7"/2.0	0.307	100	58
4692-02M-BB	13A/125V	16/3 (26x30)*	CEE	6'7"/2.0	0.334	100	57

Standard Hank Packaged

*Stock also produced with Alternate Stranding of 65x34

TYPE SJT

Unshielded, PVC Jacket, 60°C



End One: UC-07H (NEMA 6-20P)

End Two: UC-033R (IEC 60320/C19)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4262-76I-BB	20A/250V	12/3 (65x30)	CEE	7'6"/2.3	0.429	25	35

Standard Hank Packaged

TYPE NISPT-2

PVC Jacket, 105°C



End One: UC-001 (NEMA 1-15P)

End Two: UC-03C/H (IEC 60320/C7)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
1840-25M-BB	7A/125V	18/2 (41x34)	CEE	8'2"/2.5	0.139/0.271	125	35

Standard Hank Packaged

NOTE: BB = Black, GG = Gray



3 Conductor Electronic Jumper Cords

North American



TYPE SVT

Foil Shielded, PVC Jacket, 60°C



End One: UC-009 (IEC 60320/C14)

End Two: UC-005 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
5835-01M-BB	10A-125V/250V	18/3 (41x34)	CEE	3'3"/1.0	0.263	100	27

Braided Shield available upon request as a custom item.
Standard Bulk Packaged.

TYPE SJT

Foil Shielded, PVC Jacket, 60°C



End One: UC-009 (IEC 60320/C14)

End Two: UC-005 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
6835-01M-BB	10A-125V/250V	18/3 (41x34)	CEE	3'3"/1.0	0.343	100	29
6635-01M-BB	13A-125V/250V	16/3 (65x34)	CEE	3'3"/1.0	0.360	100	33

Braided Shield available upon request as a custom item.
Standard Bulk Packaged.

TYPE SVT

Unshielded, PVC Jacket, 60°C



End One: UC-009 (IEC 60320/C14)

End Two: UC-005 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
3835-01M-BB	10A-125V/250V	18/3 (41x34)	CEE	3'3"/1.0	0.255	100	26
3835-02M-BB	10A-125V/250V	18/3 (41x34)	CEE	6'7"/2.0	0.255	100	37

Standard Bulk Packaged

NOTE: BB = Black, GG = Gray
*Carries both 125V & 250V Rating



UNICABLE
www.unicable.com

California: (800) GET-CORD
Kentucky: (800) FOR-CORD

FAX: (714) 761-0569
FAX: (270) 843-8888

3 Conductor Electronic Jumper Cords

International



TYPE SJT

Unshielded, PVC Jacket, 60°C



End One: UC-009 (IEC 60320/C14)

End Two: UC-005 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4835-01M-BB	10A-125V/250V	18/3 (41x34)	CEE	3'3"/1.0	0.307	100	30
4835-02M-BB	10A-125V/250V	18/3 (41x34)	CEE	6'7"/2.0	0.307	100	44
4635-02M-BB	13A-125V/250V	16/3 (26x30)*	CEE	6'7"/2.0	0.334	75	45

Standard Bulk Packaged

*Stock also produced with Alternate Stranding of 65x34

TYPE H05VV-F/SJT

PVC Jacket, 70°C/60°C



End One: UC-09I (IEC 60320/C14)

End Two: UC-05I (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
8135-02M-BB	10A/250V	1.0mm ² /18x3C	CEE	6'7"/2.0	0.300	100	52

Standard Bulk Packaged

TYPE H05VV-F

PVC Jacket, 70°C



End One: UC-09I (IEC 60320/C14)

End Two: UC-05I (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8145-02M-BB	10A/250V	1.0mm ² x 3C	CEE	6'7"/2.0	7.1	100	43

Standard Bulk Packaged

NOTE: BB = Black, GG = Gray



3 Conductor Hospital Grade Power Supply Cords

North American Color Code



TYPE SJT

PVC Jacket, 60°C/105°C, VW-1



End One: UC-018 (NEMA 5-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4880-03M-BB	10A/125V	18/3 (41x34)	NA	9'10"/3.0	0.307	50	39
4880-03M-GG	10A/125V	18/3 (41x34)	NA	9'10"/3.0	0.307	50	39
4881-03M-GG**	10A/125V	18/3 (41x34)	NA	9'10"/3.0	0.307	50	39
4680-04M-BB	13A/125V	16/3 (65x34)	NA	13'1"/4.0	0.334	50	57
4680-04M-GG	13A/125V	16/3 (65x34)	NA	13'1"/4.0	0.334	50	57
4480-04M-GG	15A/125V	14/3 (41x30)	NA	13'1"/4.0	0.375	25	37

Standard Coil & Tie Packaged

TYPE SJT

PVC Jacket, 60°C/105°C, VW-1



End One: UC-018A (NEMA 5-15P)

End Two: Remove Outer Jacket 2", Strip & Twist 5/8"



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4870-03M-GG	10A/125V	18/3 (41x34)	NA	9'10"/3.0	0.307	50	38

Standard Coil & Tie Packaged

Green dot on face of plug designates approval for hospital grade use.

U-Shaped grounding pin is used on hospital grade plugs.

**Denotes Clear PVC male plug.

NOTE: BB = Black, GG = Gray



UNICABLE
www.unicable.com

California: (800) GET-CORD

Kentucky: (800) FOR-CORD

FAX: (714) 761-0569

FAX: (270) 843-8888

3 Conductor Hospital Grade Detachable Cords

North American Color Code



TYPE SJT

PVC Jacket, 60°C/105°C, VW-1



End One: UC-018 (NEMA 5-15P)

End Two: UC-005 (IEC 60320/



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4810-03M-BB	10A/125V	18/3 (41x34)	NA	9'10" / 3.0	0.307	50	40
4810-03M-GG	10A/125V	18/3 (41x34)	NA	9'10" / 3.0	0.307	50	40
4811-03M-GG*	10A/125V	18/3 (41x34)	NA	9'10" / 3.0	0.307	50	40

Standard Coil & Tie Packaged

*Denotes Clear Plug

TYPE SJT

PVC Jacket, 60°C/105°C, VW-1



C13)

End One: UC-018A (NEMA 5-15P)

End Two: UC-005 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD INCHES	STD PKG.	PKG WT LBS.
4820-03M-GG	10A/125V	18/3 (41x34)	NA	9'10" / 3.0	0.307	50	40
4622-04M-BB**	13A/125V	16/3 (26x30)*	NA	13'1" / 4.0	0.334	25	32

Standard Coil & Tie Packaged

Green dot on face of plug designates approval for hospital grade use.

U-Shaped grounding pin is used on hospital grade plugs.

*Stock also produced with Alternate Stranding of 65x34

**Denotes Clear PVC male plug with built-in lamp for added safety (UC-018AL, UL/CUL only)

NOTE: BB = Black, GG = Gray



International Power Supply Cords

Continental Europe



TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable



End One: UC-813 (CEE 7/7)

End Two: Remove Outer Jacket 50mm, Strip & Tin 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8100-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	26
8100-25M-GG	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	26

Standard Bulk Packaged
Stranding: 32x0.20

TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable



End One: UC-814 (CEE 7/7)

End Two: Remove Outer Jacket 50mm, Strip & Tin 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8110-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	28

Standard Bulk Packaged
Stranding: 32x0.20

TYPE H05VV-F

PVC Jacket, 70°C, Detachable



End One: UC-813 (CEE 7/7)

End Two: UC-05I (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8150-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	31
8150-25M-GG	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	31

Standard Hank Packaged
Stranding: 32x0.20

NOTE: BB = Black, GG = Gray

International Power Supply Cords

Continental Europe



TYPE H05VV-F

PVC Jacket, 70°C, Detachable



End One: UC-814 (CEE 7/7)
End Two: UC-05I (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8192-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	31
8192-25M-GG	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	31

Standard Hank Packaged
Stranding: 32x0.20

TYPE H03VVH2-F

PVC Jacket, 70°C, Non-Detachable



End One: UC-811 (CEE 7/16)
End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8120-25M-BB	2.5A/250V	0.75mm ² x 2C	CEE	8'2"/2.5	3.4/5.6	100	25

Standard Bulk Packaged
Stranding: 24x0.20

TYPE H03VVH2-F

PVC Jacket, 70°C, Detachable



End One: UC-811 (CEE 7/16)
End Two: UC-03C/H (IEC 60320/C7)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8125-25M-BB	2.5A/250V	0.75mm ² x 2C	CEE	8'2"/2.5	3.4/5.6	100	27

Standard Hank Packaged
Stranding: 24x0.20

NOTE: BB = Black, GG = Gray



International Power Supply Cords

Switzerland/UK (Great Britain)



SWITZERLAND TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable



End One: UC-841 (SEV 1011)

End Two: Remove Outer Jacket 50mm, Strip & Tin 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8400-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	27

Standard Bulk Packaged
Stranding: 32x0.20

TYPE H05VV-F

PVC Jacket, 70°C, Detachable



End One: UC-841 (SEV 1011)

End Two: UC-051 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8450-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	30

Standard Hank Packaged
Stranding: 32x0.20

UK (GREAT BRITAIN) TYPE H05VV-F

PVC Jacket, 70°C,
Non-Detachable



End One: BS1363

End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.	FUSE RATING
8500-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	6.90	50	34	10A
8501-25M-BB	13A/250V	1.5mm ² x 3C	CEE	8'2"/2.5	8.0-9.8	50	39	13A

Standard Bulk Packaged
BSI or ASTA approvals on plug.
Stranding: 32x0.20

TYPE H05VV-F

PVC Jacket, 70°C,
Detachable



End One: BS1363

End Two: UC-051 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.	FUSE RATING
8550-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	6.9	50	36	10A

Standard Bulk Packaged
BSI or ASTA approvals on plug.
Stranding: 32x0.20

NOTE: BB = Black, GG = Gray

International Power Supply Cords

Denmark/Italy



DENMARK TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable

End One: UC-881 (AFSNIT 107-2-D1)

End Two: Remove Outer Jacket 50mm, Strip & Tin 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8800-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	28
Standard Bulk Packaged Stranding: 32x0.20							

TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable

End One: UC-882 (AFSNIT 107-2-D1)

End Two: Remove Outer Jacket 50mm, Strip & Tin 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8801-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	28
Standard Bulk Packaged Stranding: 32x0.20							

TYPE H05VV-F

PVC Jacket, 70°C, Detachable

End One: UC-882 (AFSNIT 107-2-D1)

End Two: UC-051 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8850-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	31
Standard Hank Packaged Stranding: 32x0.20							

ITALY TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable

End One: UC-861 (CEI 23-16-VII)

End Two: Remove Outer Jacket 50mm, Strip & Tin 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8600-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	25
Standard Bulk Packaged Stranding: 32x0.20							

TYPE H05VV-F

PVC Jacket, 70°C, Detachable

End One: UC-861 (CEI 23-16-VII)

End Two: UC-051 (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8650-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	28
Standard Hank Packaged Stranding: 32x0.20							

NOTE: BB = Black, GG = Gray



International Power Supply Cords

Australia/New Zealand



AUSTRALIA/NEW ZEALAND TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable



End One: UC-822 (AS/NZS 3112)

End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8200-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	28

Standard Bulk Packaged
Stranding: 32x0.20

TYPE H05VV-F

PVC Jacket, 70°C, Detachable



End One: UC-822 (AS/NZS 3112)

End Two: UC-05I (IEC 60320/C13)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8250-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	30
8250-25M-GG	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	30

Standard Hank Packaged
Stranding: 32x0.20

TYPE H03VVH2-F

PVC Jacket, 70°C, Non-Detachable



End One: UC-821 (AS/NZS 3112)

End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8220-25M-BB	7.5A/250V	0.75mm ² x 2C	CEE	8'2"/2.5	3.4/5.6	100	32

Standard Bulk Packaged
Stranding: 24x0.20

TYPE H03VVH2-F

PVC Jacket, 70°C, Detachable



End One: UC-821 (AS/NZS 3112)

End Two: UC-03C/H (IEC 60320/C7)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8225-25M-BB	2.5A/250V	0.75mm ² x 2C	CEE	8'2"/2.5	3.4/5.6	100	34

Standard Hank Packaged
Stranding: 24x0.20

NOTE: BB = Black, GG = Gray



UNICABLE
www.unicable.com

California: (800) GET-CORD
Kentucky: (800) FOR-CORD

FAX: (714) 761-0569
FAX: (270) 843-8888

International Power Supply Cords

Japan



JAPAN TYPE VCTF

PVC Jacket, 60°C, Non-Detachable



End One: UC-832 (JIS 8303)

End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8300-25M-BB	15A/125V	2.0mm ² x 3C 37/0.26	NA	8'2"/2.5	8.5	50	37
8301-25M-BB	7A/125V	0.75mm ² x 3C 30/0.18	NA	8'2"/2.5	7.0	100	47

Standard Bulk Packaged

TYPE VCTF

PVC Jacket, 60°C, Detachable



End One: UC-832 (JIS 8303)

End Two: UC-837 (IEC 60320/C13)

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8350-25M-BB	12A/125V	2.0mm ² x 3C 41/0.25	NA	8'2"/2.5	8.5	75	62
8351-25M-BB	7A/125V	0.75mm ² x 3C 30/0.18	NA	8'2"/2.5	7.0	100	50

Standard Hank Packaged

TYPE HVCTFK

PVC Jacket, 75°C, Non-Detachable



End One: UC-830 (JIS 8303)

End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8320-25M-BB	7A/125V	0.75mm ² x 2C 30/0.18	NA	8'2"/2.5	4.3/6.6	150	45

Standard Bulk Packaged

TYPE VCTFK

PVC Jacket, 75°C, Detachable



End One: UC-830 (JIS 8303)

End Two: UC-839 (IEC 60320/C7)

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8325-25M-BB	7A/125V	0.75mm ² x 2C 30/0.16	NA	8'2"/2.5	4.3/6.6	100	28

Standard Hank Packaged

NOTE: BB = Black, GG = Gray



International Power Supply Cords

China/Israel



CHINA TYPE RVV

PVC Jacket, 70°C, Non-Detachable



End One: UC-053 (GB 1002-1996)

End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8530-25M-BB <i>Standard Bulk Packaged Stranding: 32x0.20</i>	10A/250V	1.00mm ² x 3C	CEE	8'2"/2.5	7.1	50	28

TYPE RVV

PVC Jacket, 70°C, Detachable



End One: UC-053(GB 1002-1996)

End Two: UC-052 (GB 1002-1996)



PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8535-25M-BB <i>Standard Hank Packaged Stranding: 32x0.20</i>	10A/250V	1.00mm ² x 3C	CEE	8'2"/2.5	7.1	50	30

ISRAEL TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable



End One: UC-891(SI 32)

End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8900-25M-BB <i>Standard Bulk Packaged Stranding: 32x0.20</i>	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	28

TYPE H05VV-F

PVC Jacket, 70°C, Detachable



End One: UC-891(SI 32)

End Two: UC-051 (IEC 60320/C13)

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8950-25M-BB <i>Standard Hank Packaged Stranding: 32x0.20</i>	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	31

NOTE: BB = Black, GG = Gray



UNICABLE
www.unicable.com

California: (800) GET-CORD
Kentucky: (800) FOR-CORD

FAX: (714) 761-0569
FAX: (270) 843-8888

International Power Supply Cords

Argentina/South Africa/India



ARGENTINA TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable



End One: UC-897(No Approvals)

End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8960-25M-BB	10A/220V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	28
Standard Bulk Packaged Stranding: 32x0.20							

TYPE H05VV-F

PVC Jacket, 70°C, Detachable



End One: UC-897(No Approvals)

End Two: UC-05I (IEC 60320/C13)

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8965-25M-BB	10A/220V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	30
Standard Hank Packaged Stranding: 40x0.18							

SOUTH AFRICA/INDIA TYPE H05VV-F

PVC Jacket, 70°C, Non-Detachable



End One: UC-871(No Approvals)

End Two: Remove Outer Jacket 50mm, Strip & Twist 12mm

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8700-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	32
Standard Bulk Packaged Stranding: 32x0.20							

TYPE H05VV-F

PVC Jacket, 70°C, Detachable



End One: UC-871(No Approvals)

End Two: UC-05I (IEC 60320/C13)

PART NUMBER	RATING	AWG SIZE & STRANDING	COLOR CODE	LENGTH FT/MTRS.	NOM OD mm	STD PKG.	PKG WT LBS.
8750-25M-BB	10A/250V	1.0mm ² x 3C	CEE	8'2"/2.5	7.1	50	34
Standard Hank Packaged Stranding: 32x0.20							

NOTE: BB = Black, GG = Gray

